

**MATERIAL SAFETY DATA SHEET****S-OIL SEVEN 4T RIDER #5 SG 15W-40**

Date of the previous version: 2019-06-19

Revision Date: 2020-10-06

Version 2.2

**1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1. Product identifier**

Product name S-OIL SEVEN 4T RIDER #5 SG 15W-40  
Pure substance/mixture Mixture

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Recommended Use 4 Cycle motor oil

**1.3. Details of the supplier of the safety data sheet**

Supplier S-OIL CORPORATION  
192, Baekbeom-ro, Mapo-gu,  
Seoul 04196, Korea

**For further information, please contact:**

Contact Point HSSEQ  
E-mail Address dolyoo@s-oil-total.com

**1.4. Emergency telephone number**

Korea + 82 2 527-6052

**2. HAZARDS IDENTIFICATION****2.1. Classification of the substance or mixture**

GHS Classification

Not classified as hazardous.

**2.2. Label elements**

GHS label elements, including precautionary statements

Symbol(s) Not Classified

Signal Words Not Classified

**2.3. GHS Hazard Statements**

Not Classified

**2.4. GHS Precautionary Statements**

Prevention Not Classified

Response Not Classified

Storage Not Classified

Disposal Not Classified

## MATERIAL SAFETY DATA SHEET

# S-OIL SEVEN 4T RIDER #5 SG 15W-40

Date of the previous version: 2019-06-19

Revision Date: 2020-10-06

Version 2.2

### 2.5. Other hazards

**Physical-Chemical Properties** Contaminated surfaces will be extremely slippery.

**Environmental properties** Should not be released into the environment

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixture

Chemical Name	CAS-No	EC-No	Weight %
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	76.0 ~ 84.0
Mixed performance additive	Mixture	-	5.0 ~ 10.0
Viscosity modifier additive	Mixture	-	9.0 ~ 16.0
Oil solution of acrylic polymer	Mixture	-	< 1.0

**Additional information** Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

## 4. FIRST AID MEASURES

### 4.1. Description of first-aid measures

**General advice** IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

**Eye contact** Rinse thoroughly with plenty of water, also under the eyelids.

**Skin contact** Remove contaminated clothing and shoes. Wash skin with soap and water. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. In this case, the casualty should be sent immediately to hospital.

**Inhalation** Move to fresh air.

**Ingestion** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

**Eye contact** Not classified.

**Skin contact** Not classified. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent.

**Inhalation** Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.

**Ingestion** Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** Treat symptomatically.

## MATERIAL SAFETY DATA SHEET

### S-OIL SEVEN 4T RIDER #5 SG 15W-40

Date of the previous version: 2019-06-19

Revision Date: 2020-10-06

Version 2.2

#### 5. FIRE-FIGHTING MEASURES

##### 5.1. Extinguishing media

Suitable extinguishing media CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam.

Unsuitable extinguishing media No information available

##### 5.2. Special hazards arising from the substance or mixture

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.

##### 5.3. Advice for fire-fighters

Special protective equipment for fire-fighters Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

#### 6. ACCIDENTAL RELEASE MEASURES

##### 6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery.  
Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

##### 6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses.  
Local authorities should be advised if significant spillages cannot be contained.

##### 6.3. Methods and material for containment and cleaning up

Methods for containment Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.

##### 6.4. Reference to other sections

Personal Protective Equipment See Section 8 for more detail.

Waste treatment See section 13.

#### 7. HANDLING AND STORAGE

##### 7.1. Precautions for safe handling

Advice on safe handling When using, do not eat, drink or smoke. For personal protection see section 8.

## MATERIAL SAFETY DATA SHEET

### S-OIL SEVEN 4T RIDER #5 SG 15W-40

Date of the previous version: 2019-06-19

Revision Date: 2020-10-06

Version 2.2

	Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.
<b>Prevention of fire and explosion</b>	Take precautionary measures against static discharges. Ground/bond containers, tanks and transfer/receiving equipment.
<b>Hygiene measures</b>	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

#### **7.2. Conditions for safe storage, including any incompatibilities**

<b>Technical measures/Storage conditions</b>	Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.
<b>Materials to Avoid</b>	Strong oxidizing agents.

#### **7.3. Specific end uses**

### **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### **8.1. Control parameters**

<b>Exposure limits</b>	oil mist : 10mg/m <sup>3</sup> , for 15 minutes; oil mist : 5mg/m <sup>3</sup> , for 8 hours
<b>Legend</b>	See section 16.

#### **8.2. Exposure controls**

##### **Occupational Exposure Controls**

<b>Engineering Measures</b>	Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.
-----------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

##### **Personal Protective Equipment**

<b>General Information</b>	If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.
<b>Respiratory protection</b>	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.
<b>Eye Protection</b>	If splashes are likely to occur, wear: Safety glasses with side-shields.
<b>Skin and body protection</b>	Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.
<b>Hand Protection</b>	Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the

## MATERIAL SAFETY DATA SHEET

# S-OIL SEVEN 4T RIDER #5 SG 15W-40

Date of the previous version: 2019-06-19

Revision Date: 2020-10-06

Version 2.2

instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves.

### Environmental exposure controls

**General Information**                      The product should not be allowed to enter drains, water courses or the soil.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Color Physical State @20°C Odor		Amber liquid Characteristic	
<b><u>Property</u></b> pH Boiling point/boiling range	<b><u>Values</u></b>	<b><u>Remarks</u></b> Not applicable Not applicable	<b><u>Method</u></b>
Flash point	234 °C 453.2 °F		Cleveland Open Cup (COC) Cleveland Open Cup (COC)
Evaporation rate Flammability Limits in Air Vapor Pressure Vapor density		No information available No information available No information available No information available	
Density Water solubility Solubility in other solvents logPow	877.5 kg/m <sup>3</sup> Negligible	@ 15 °C Insoluble No information available No information available	
Autoignition temperature Viscosity, kinematic	121.50 mm <sup>2</sup> /s 15.90 mm <sup>2</sup> /s	No information available @ 40 °C @ 100 °C	
Explosive properties Oxidizing Properties Possibility of hazardous reactions	Not explosive Not applicable Not applicable		

### 9.2. Other information

## 10. STABILITY AND REACTIVITY

### 10.1. Reactivity

**General Information**                      No information available.

### 10.2. Chemical stability

**Stability.**                                      Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous Reactions**                      None under normal processing.

### 10.4. Conditions to Avoid

**Conditions to Avoid**                      Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

**MATERIAL SAFETY DATA SHEET**

**S-OIL SEVEN 4T RIDER #5 SG 15W-40**

Date of the previous version: 2019-06-19

Revision Date: 2020-10-06

Version 2.2

**10.5. Incompatible Materials**

**Materials to Avoid** Strong oxidizing agents.

**10.6. Hazardous Decomposition Products**

**Hazardous Decomposition Product** None under normal use.

**11. TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

**Acute toxicity Local effects Product Information**

**Skin contact** . Not classified. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent.

**Eye contact** . Not classified.

**Inhalation** . Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.

**Ingestion** . Not classified.

**Acute toxicity - Component Information**

Chemical name	Oral	Dermal	Inhalation
Distillates (petroleum), hydrotreated heavy paraffinic	LD50 > 5000 mg/kg bw (rat – OECD 420)	LD50 > 5000 mg/kg bw (rabbit – OECD 402)	LC50 > 5 mg/l (4h, aerosol) (rat – OECD 403)
Oil solution of acrylic polymer	LD50 > 2000 mg/kg (rat)	LD50 > 2000 mg/kg (rabbit)	-

**Skin corrosion/irritation**

Chemical name	Skin corrosion/irritation
Mixed performance additive	Classification: Irritating. Rabbit. Remarks: Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying and cracking of the skin. Causes skin irritation.

**Serious eye damage/eye irritation**

Chemical name	Serious eye damage/eye irritation
Mixed performance additive	Classification: Not irritating. Rabbit. Remarks: Not classified as a primary eye irritant.

**Sensitization**

**Sensitization** Not classified as a sensitizer.

**Specific effects**

**Carcinogenicity** This product is not classified carcinogenic.  
**Mutagenicity** This product is not classified as mutagenic.  
**Reproductive toxicity** This product does not present any known or suspected reproductive hazards.

**Repeated Dose Toxicity**

**Subchronic toxicity** No information available.

## MATERIAL SAFETY DATA SHEET

### S-OIL SEVEN 4T RIDER #5 SG 15W-40

Date of the previous version: 2019-06-19

Revision Date: 2020-10-06

Version 2.2

**Target Organ Effects (STOT)**

Target Organ Effects (STOT) No information available.

**Other information**

Other adverse effects Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).

**12. ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**Acute aquatic toxicity - Component Information**

Chemical name	Toxicity algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish
Distillates (petroleum), hydrotreated heavy paraffinic	EL50 > 100 mg/l (48h, Pseudokirchnerella subcapitata – OECD 201)	EL50 > 10000 mg/l (48h, Daphnia magna – OECD 202)	LL50 > 100 mg/l (96h, Oncorhynchus mykiss – OECD 203)

**Chronic aquatic toxicity - Component Information**

Chemical name	Toxicity algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish
Distillates (petroleum), hydrotreated heavy paraffinic	-	NOEL 10 mg/l (21d, Daphnia magna – QSAR Petrotox)	NOEL > 1000 mg/l (14/28d, Oncorhynchus mykiss – QSAR Petrotox)

Effects on terrestrial organisms No information available.

**12.2. Persistence and degradability**

General Information No information available.

**12.3. Bioaccumulative potential**

Product Information No information available.

logPow No information available

Component Information No information available.

**12.4. Mobility in soil**

Soil Given its physical and chemical characteristics, the product generally shows low soil mobility.

Air Loss by evaporation is limited.

Water Insoluble. The product spreads on the surface of the water.

**12.5. Results of PBT and vPvB assessment**

PBT and vPvB assessment No information available.

**12.6. Other adverse effects**

General Information No information available

**MATERIAL SAFETY DATA SHEET****S-OIL SEVEN 4T RIDER #5 SG 15W-40**

Date of the previous version: 2019-06-19

Revision Date: 2020-10-06

Version 2.2

**13. DISPOSAL CONSIDERATIONS****13.1. Waste treatment methods**

<b>Waste from Residues / Unused Products</b>	Should not be released into the environment. Do not empty into drains. Dispose of in accordance with all applicable national environmental laws and regulations. Where possible recycling is preferred to disposal or incineration.
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal.
<b>EWC Waste Disposal No.</b>	The following Waste Codes are only suggestions: 13 01 10. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

**14. TRANSPORT INFORMATION**

<b>ADR/RID</b>	Not regulated
<b>IMDG/IMO</b>	Not regulated
<b>ICAO/IATA</b>	Not regulated
<b>ADN</b>	Not regulated

**15. REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****International Inventories**

TSCA

KECL

**Legend**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

KECL - Korean Existing and Evaluated Chemical Substances

**Further information****15.2. Chemical Safety Assessment**

Chemical Safety Assessment No information available

**16. OTHER INFORMATION****Abbreviations, acronyms**

Legend Section 8

+	Sensitizer	*	Skin designation
**	Hazard Designation	C:	Carcinogen
M:	Mutagen	R:	Toxic to reproduction

Revision Date: 2020-10-06



## MATERIAL SAFETY DATA SHEET

---

### S-OIL SEVEN 4T RIDER #5 SG 15W-40

Date of the previous version: 2019-06-19

Revision Date: 2020-10-06

Version 2.2

---

**Revision Note**

\*\*\* Indicates updated section.

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet