

Product Description

S-OIL SEVEN 4T RIDER #5 SM/MA is multi grade engine oil specially designed for use in modern 4-stroke motorcycle. Its high viscosity index and purity provide excellent oxidation stability and cleanliness of engine.

Applications

- O All type of modern 4-stroke motorcycle engines of all cubic capacities, for most severe condition of use
- O Adapted for gear boxes lubrication and oil immersed clutches

Features and Potential Benefits

- $\ensuremath{\mathbb{O}}$ Very high viscosity index and good viscosity stability in operation
- O Excellent resistance of the oil film at high temperatures and resistance to oxidation
- O Very high level of detergency and dispersion properties
- O Very good anti-wear, anti-corrosion, anti-rust and anti-foaming properties

Performance Level

- O API : SM
- O JASO : MA

Typical Properties

-	Test Items	Method	Unit	20W-40	20W-50
Specific Gravity		ASTM D1298	-	0.881	0.884
Viscosity	40° C	ASTM D445	cSt	118.5	159.7
	100 ℃	ASTM D445	cSt	13.6	17.8
Viscosity Index		ASTM D2270	-	111	123
Flash Point		ASTM D92	°C	256	236
Pour Point		ASTM D97	°C	-32	-30

S-OIL CORPORATION 192, Baekbeom-ro, Mapo-gu,	S-OIL SEVEN 4T RIDER #5 SM/MA 2019.06.20	
Seoul, 04196, Korea		-049_000_ ·· _000_000_

This lubricant used recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet is obtainable via your commercial adviser.