

Certificate of Analysis

PRODUCT : S-OIL 7 ATF DEXRON VI-EX (200)

CERT. NO. : 20220622-0066

D A T E : 2022/06/22

CUSTOMER : S-OIL

TANK No. : IBT-03


DATE SAMPLED : 2022/04/22

LOT No. : 221438

TEST ITEMS	UNIT	TEST METHOD	RESULTS
Color		ASTM D 1500	L7.0
Density, 15	g/cm ³	ASTM D 4052	0.8479
Viscosity, 40	cSt	ASTM D 445	31.61
Viscosity, 100	cSt	ASTM D 445	6.281
Viscosity Index		ASTM D 2270	154
Flash Point, COC		ASTM D 92	216
Pour Point		ASTM D 97	-48
Foaming Test Tendency/Stability, Sequence 1	ml	ASTM D 892	10/0
Foaming Test Tendency/Stability, Sequence 2	ml	ASTM D 892	20/0
Foaming Test Tendency/Stability, Sequence 3	ml	ASTM D 892	10/0

I CERTIFY THE ABOVE TEST RESULTS ARE TRUE AND CORRECT.

Chief Chemist
JB.Shin



S-OIL TotalEnergies Lubricants Co., Ltd.

Head Office : 16F, HSBC Building, 37, Chilpae-ro, Jung-gu, Seoul, Korea Tel.+82 2 6320 2000 Fax. +82 2 6320 2100
Plant : 436, Dangwol-ro, Onsan-eup, Ulju-gun, Ulsan, Korea Tel.+82 52 240 3133 Fax. +82 52 240 3134