


Certificate of Analysis

PRODUCT : S-OIL 7 RED #9 LPG 10W-30-EX (200)
CERT. NO. : 20220622-0022 D A T E : 2022/06/22
CUSTOMER : S-OIL (주) 온산공장 TANK No. : OBT-11
DATE SAMPLED : 2021/11/12 LOT No. : 214295

TEST ITEMS	UNIT	TEST METHOD	RESULTS
Color		ASTM D 1500	L3.0
Density, 15℃	g/cm ³	ASTM D 4052	0.8526
Viscosity, 40℃	cSt	ASTM D 445	69.33
Viscosity, 100℃	cSt	ASTM D 445	11.06
Viscosity Index		ASTM D 2270	151
C.C.S., -25℃	cP	ASTM D 5293	5150
T.B.N	mgKOH/g	ASTM D 2896	7.27
Flash Point, COC	℃	ASTM D 92	244
Pour Point	℃	ASTM D 97	-33
Foaming Test Tendency/Stability, Sequence 1	ml	ASTM D 892	10/0
Foaming Test Tendency/Stability, Sequence 2	ml	ASTM D 892	20/0
Foaming Test Tendency/Stability, Sequence 3	ml	ASTM D 892	10/0

I CERTIFY THE ABOVE TEST RESULTS ARE TRUE AND CORRECT.

Chief Chemist
JB.Shin



S-OIL TotalEnergies Lubricants Co., Ltd.

Head Office : 16F, HSBC Building, 37, Chilpae-ro, Jung-gu, Seoul, Korea Tel.+82 2 6320 2000 Fax. +82 2 6320 2100
Plant : 436, Dangwol-ro, Onsan-eup, Ulju-gun, Ulsan, Korea Tel.+82 52 240 3133 Fax. +82 52 240 3134