



S-OIL SEVEN ATF DEXRON VI

SYNTHETIC AUTOMATIC TRANSMISSION FLUID

Product Description

S-OIL SEVEN ATF DEXRON VI is a high performance automatic transmission fluid officially approved by General Motors (License Number J-60007) for use in vehicles with automatic transmissions. It is formulated with 100% synthetic base stocks and advanced additive technology. It is also fully back serviceable and can be used wherever DEXRON II and/or DEXRON III are recommended.

Applications

- It is recommended for all 2006 and beyond GM's vehicles with automatic transmissions
- It is also fully back serviceable and can be used wherever DEXRON II and/or DEXRON III are recommended

Features and Potential Benefits

- Extended drain intervals and consistent shift performance
- Protect against wear, corrosion and the formation of harmful deposits such as lacquers and sludge
- Excellent thermal stability and resistance to oxidation
- Very good viscosity stability in operation
- Exceptional friction and anti-shudder performances
- Enhanced fuel economies thanks to low viscosity and excellent low temperature performance

Performance Level

- GM : DEXRON VI
- Ford : MERCON/FORD M2C 138CJ/166H
- Mercedes Benz : 236.6/7/9
- JASO : 1A-LV
- Honda : DW-1
- Hyundai/Kia : SP-IV
- Mazda : ATF FZ/F-1/S-1
- Mitsubishi : DIAQUEEN J2/3/ATF PA
- Nissan : MATIC K/S
- Toyota : ATF T-IV/WS
- ZF : TE-ML 09/09X/11A/11B

Typical Properties

Test Items	Method	Unit	Properties
Specific Gravity	ASTM D1298	-	0.846
Viscosity	ASTM D445	cSt	29.5
	ASTM D445	cSt	6.0
Viscosity Index	ASTM D2270	-	159
Flash Point	ASTM D92	°C	222
Pour Point	ASTM D97	°C	-45

S-OIL CORPORATION
192, Baekbeom-ro, Mapo-gu,
Seoul, 04196, Korea

S-OIL SEVEN ATF DEXRON VI
2019.06.20



This lubricant used recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet is obtainable via your commercial adviser.