

S-OIL SEVEN RED #5 SG

MULTI GRADE OIL FOR GASOLINE ENGINE OIL

Product Description

S-OIL SEVEN RED #5 SG is multi grade engine oil for all gasoline engines. It suitable for recent technology engines (multi valve, turbocharged, with/without catalytic converter) and vehicles requiring performance specification API SG.

Applications

- All gasoline engines, especially for most recent technology engines (multi valve, turbocharged, with/without catalytic converter) supercharged or not, in cars
- O Suitable for all journeys (in town, on highways) and particularly in severe conditions
- O For all driving styles, vigorous speeds in all seasons

Features and Potential Benefits

- O Very high viscosity index and good viscosity stability in operation
- O Exceptional detergency level and soot dispersion properties
- O High performance level insures safer and longer drains intervals

Performance Level

O API : SJ/SG/CF

Typical Properties

| J I · · · · · | | | | |
|----------------------|--------------|------------|------|--------|
| Test Items | | Method | Unit | 15W-40 |
| Specific Gravity | | ASTM D1298 | - | 0.870 |
| Viscosity | 40 °C | ASTM D445 | cSt | 108.9 |
| | 100 ℃ | ASTM D445 | cSt | 14.5 |
| Viscosity Index | | ASTM D2270 | - | 136 |
| HTHS Viscosity | | ASTM D4683 | - | 4.0 |
| Flash Point | | ASTM D92 | °C | 236 |
| Pour Point | | ASTM D97 | °C | -36 |
| | | | | |

| S-OIL CORPORATION | S-OIL SEVEN RED #5 SG | | |
|----------------------------|-----------------------|--|--|
| 192, Baekbeom-ro, Mapo-gu, | 2020.01.06. | | |
| Seoul, 04196, Korea | | | |

This lubricant used recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet is obtainable via your commercial adviser.