

Certificate of Analysis

PRODUCT : S-OIL 7 ATF MULTI-EX (P1x12)

CERT. NO. : 20250801-0027

D A T E : 2025/08/01

CUSTOMER : S-OIL

TANK No. : OBT-13


DATE SAMPLED : 2025/06/26

LOT No. : 252219

TEST ITEMS	UNIT	TEST METHOD	RESULTS
Color		ASTM D 1500	Red
Density, 15	g/cm ³	ASTM D 4052	0.8462
Viscosity, 40	cSt	ASTM D 445	36.34
Viscosity, 100	cSt	ASTM D 445	6.918
Viscosity Index		ASTM D 2270	153
Flash Point, COC		ASTM D 92	226
Pour Point		ASTM D 97	-48
Foaming Test Tendency/Stability, Sequence 1	ml	ASTM D 892	10/0
Foaming Test Tendency/Stability, Sequence 2	ml	ASTM D 892	30/0
Foaming Test Tendency/Stability, Sequence 3	ml	ASTM D 892	10/0

I CERTIFY THE ABOVE TEST RESULTS ARE TRUE AND CORRECT.

Chief Chemist
JB.Shin



S-OIL TotalEnergies Lubricants Co., Ltd.

Head Office : 16F, HSBC Building, 37, Chilpae-ro, Jung-gu, Seoul, Korea Tel.+82 2 6320 2000 Fax. +82 2 6320 2100
Plant : 436, Dangwol-ro, Onsan-eup, Ulju-gun, Ulsan, Korea Tel.+82 52 240 3133 Fax. +82 52 240 3134