

Certificate of Analysis

PRODUCT : S-OIL 7 GOLD #9 PAO C3 5W-30-EX (P1x12)

CERT. NO. : 20250801-0038

D A T E : 2025/08/01

CUSTOMER : S-OIL

TANK No. : KD(BLENDING)


DATE SAMPLED : 2025/05/26

LOT No. : 259060

TEST ITEMS	UNIT	TEST METHOD	RESULTS
Color		ASTM D 1500	L2.5
Density, 15	g/cm ³	ASTM D 4052	0.8487
Viscosity, 40	cSt	ASTM D 445	69.50
Viscosity, 100	cSt	ASTM D 445	12.11
Viscosity Index		ASTM D 2270	173
C.C.S., -30	cP	ASTM D 5293	5050
Flash Point, COC		ASTM D 92	234
Pour Point		ASTM D 97	-39
T.B.N	mgKOH/g	ASTM D 2896	7.75
Foaming Test Tendency/Stability, Sequence 1	ml	ASTM D 892	0/0
Foaming Test Tendency/Stability, Sequence 2	ml	ASTM D 892	20/0
Foaming Test Tendency/Stability, Sequence 3	ml	ASTM D 892	0/0

I CERTIFY THE ABOVE TEST RESULTS ARE TRUE AND CORRECT.

Chief Chemist
JB.Shin



S-OIL TotalEnergies Lubricants Co., Ltd.

Head Office : 16F, HSBC Building, 37, Chilpae-ro, Jung-gu, Seoul, Korea Tel.+82 2 6320 2000 Fax. +82 2 6320 2100
Plant : 436, Dangwol-ro, Onsan-eup, Ulju-gun, Ulsan, Korea Tel.+82 52 240 3133 Fax. +82 52 240 3134