


Certificate of Analysis

PRODUCT : S-OIL COMPRESSOR OIL RS 32-EX (200)_D
CERT. NO. : 20240321-0039 D A T E : 2024/03/21
CUSTOMER : S-OIL TANK No. : IBT-06
DATE SAMPLED : 2022/01/06 LOT No. : 220055

TEST ITEMS	UNIT	TEST METHOD	RESULTS
Aspect		Visual	Limpid
Color		ASTM D 1500	L0.5
Density, 15	g/cm ³	ASTM D 4052	0.8429
Viscosity, 40	cSt	ASTM D 445	33.57
Viscosity, 100	cSt	ASTM D 445	6.101
Viscosity Index		ASTM D 2270	130
T.A.N	mgKOH/g	ASTM D 664	0.12
Water Content	ppm	ASTM D 6304	244
Pour Point		ASTM D 97	-33
Flash Point, COC		ASTM D 92	248
Foaming Test Tendency/Stability, Sequence 1	ml	ASTM D 892	20/0
Foaming Test Tendency/Stability, Sequence 2	ml	ASTM D 892	20/0
Foaming Test Tendency/Stability, Sequence 3	ml	ASTM D 892	20/0
Copper Strip Corrosion, 100 , 3h		ASTM D 130	1a
Rust Prevention A		ASTM D 665	No rust

I CERTIFY THE ABOVE TEST RESULTS ARE TRUE AND CORRECT.

Chief Chemist
JB.Shin



S-OIL TotalEnergies Lubricants Co., Ltd.

Head Office : 16F, HSBC Building, 37, Chilpae-ro, Jung-gu, Seoul, Korea Tel.+82 2 6320 2000 Fax. +82 2 6320 2100
Plant : 436, Dangwol-ro, Onsan-eup, Ulju-gun, Ulsan, Korea Tel.+82 52 240 3133 Fax. +82 52 240 3134